



FEATURES

- **Armstrong provides one-source responsibility** for the generator system and its accessories.
- All units and components are factory tested during prototype and manufacturing stages assuring long product life.
- Generator set accepts one-step 100% of full load per NFPA 110.
- A **one-year limited warranty** covers all systems and components. Extended warranties are available.
- Rugged 4 cycle heavy-duty diesel engine, with direct fuel injection system and swirl intake ports combine for a low fuel consumption and excellent transient response.
- **Generator features:**
 - Unique Volts per Hertz compensated electronic AVR excitation system delivers reliable voltage response for in rush loads.
 - Brushless, rotating-field generator has low reactance, 2/3 pitch, class H insulation, minimizes voltage distortion when powering non-linear loads.
- **More features:**
 - Controllers are available to meet your most demanding applications.
 - In the event of low oil pressure or high coolant temperature the self-protecting system will automatically stop the engine.

GENERATOR SET RATINGS

Model	Volt Code	Voltage	Winding Connection	Phase	Power Factor	Hz	Amps Standby	Standby kW / kVA	Prime kW / kVA
A600CU	61	480 / 277	12 - HI WYE	3	0.8	60	903	600 (750)	540 (675)
A600CU	63	440 / 254	12 - HI WYE	3	0.8	60	985	600 (750)	540 (675)
A600CU	64	240 / 139	12 - HI DELTA	3	0.8	60	1806	600 (750)	540 (675)
A600CU	65	220 / 127	12 - LOW WYE	3	0.8	60	1971	600 (750)	540 (675)
A600CU	66	208 / 120	12 - LOW WYE	3	0.8	60	2084	600 (750)	540 (675)
A600CU	67	240 / 120	12 - 2 DELTA	1	1.0	60	2500	600 (600)	540 (540)
A600CU	51	415 / 240	12 - HI WYE	3	0.8	50	987	568 (710)	511 (639)
A600CU	53	380 / 220	12 - HI WYE	3	0.8	50	1080	568 (710)	511 (639)
A600CU	55	220 / 127	12 - LOW WYE	3	0.8	50	1865	568 (710)	511 (639)
A600CU	57	220 / 110	12 - 2 DELTA	1	1.0	50	2582	568 (568)	511 (511)

Stand-By ratings are continuous electrical service during the interruption of normal power. No overload capacity is specified at these ratings. Prime ratings available with variable loads are continuous, 10% overload capacity for one hour in twelve hours periods. Both ratings per BS 5514, DIN 6271, ISO-3046
Many industrial, commercial and residential voltages are available