

ARMSTRONG IV LINE

IVECO DIESEL POWERED

25 - 705 kW GENERATORS

A WIDE RANGE OF POWER SETS

Powered by one of the worlds leading manufacturers of diesel engines. Our IVECO generator line is full of standard features and ready to deliver the power you need.

STANDARD FEATURES

- Rugged and reliable 4-cycle water-cooled IVECO diesel engine.
- Brushless, class H, drip-proof.
- Industrial silencer, protective raincap, elbow pipe, installation clamps.
- Complete control panel with AC meters, engine gauges, battery charge voltmeter, phase selector switch, hourmeter and start key switch.
- Heavy-duty skid-type steel base frame.
- Integral in-base steel fuel tank with level gauge.
- Cooling radiator designed for tropical temperatures.
- Quality acrylic enamel protective paint.
- Battery, cables, rack, installation hardware.
- One year limited warranty on all components.
- Protective steel guards to isolate moving parts.
- Rubber mounting isolators between unit and frame.



OPTIONAL EQUIPMENT


- Weather and acoustic enclosures.
 - Residential and critical silencers.
 - Auto-start module.
 - Electronic speed governor.
 - Oversized fuel tank upgrade.
 - Battery trickle charger.
- Many other options available



GENERATOR SET RATINGS

GENSET MODEL	60 Hz		50 Hz		ENGINE MODEL	DIMENSIONS AND WEIGHT*			
	1800 rpm – 3 phase – 0.8 pf		1500 rpm – 3 phase – 0.8 pf			L [in]	W [in]	H [in]	Dry Wt [lb]
	STANDBY kW (kVA)	PRIME kW (kVA)	STANDBY kW (kVA)	PRIME kW (kVA)					
A30IV	31 (39)	28 (35)	28 (35)	25 (31)	8031i06	72	31	54	1508
A40IV	41 (51)	37 (46)	35 (44)	31 (39)	8041i06	78	37	54	1728
A60IV	61 (76)	56 (70)	55 (69)	50 (63)	8061i06	90	37	65	2311
A80IV	83 (104)	76 (95)	70 (88)	63 (79)	8061Si06	90	37	65	2439
A110IV	107 (134)	95 (119)	91 (114)	79 (99)	8061Si07	90	37	65	2564
A111IV	105 (131)	95 (119)	90 (113)	79 (99)	NEF45TM2	90	37	61	2336
A130IV	127 (159)	116 (145)	120 (150)	104 (130)	8061Sri26	95	37	65	2691
A135IV	135 (169)	121 (151)	118 (148)	107 (134)	NEF67TM2	105	42	62	2767
A150IV	150 (188)	137 (171)	132 (165)	120 (150)	8061SRi27	95	37	65	2789
A160IV	157 (196)	141 (176)	142 (178)	127 (159)	NEF67TM3	105	42	62	3372
A180IV	180 (225)	172 (215)	165 (206)	155 (194)	NEF60TE1	105	42	62	3442
A200IV	200 (250)	180 (225)	177 (221)	160 (200)	NEF60TE2	105	42	62	3535
A250IV	250 (313)	218 (273)	224 (280)	201 (251)	CURSOR78TE2	116	40	62	4236
A300IV	304 (380)	273 (341)	271 (339)	245 (306)	CURSOR13TE1	126	52	80	5421
A360IV	358 (448)	323 (404)	321 (401)	288 (360)	CURSOR13TE2	126	52	80	6199
A400IV	391 (489)	352 (440)	372 (465)	335 (419)	CURSOR13TE3	126	52	80	6550
A550IV	550 (688)	495 (619)	489 (611)	440 (550)	VECTOR08TE2	138	62	88	9790
A620IV	620 (775)	558 (698)	551 (689)	495 (619)	VECTOR08TE2	138	62	88	10340
A700IV	705 (881)	640 (800)	630 (788)	575 (719)	VECTOR08TE2	138	62	88	10846

Ratings: [60Hz]: 240V; [50 Hz]: 220V. Ratings applicable for both single-phase (1.0 p.f.) and 3-phase (0.8 p.f.) operation. Many industrial, commercial and residential voltages are available. Specifications are subject to change without notice. Iveco is a trademark of Varity Iveco. *1 in. = 2.54 cm; 1 Lb = 0.454 Kg.



ARMSTRONG POWER SYSTEMS

Phone (305) 470 0058 - Fax (305) 470 0068
 Toll Free (800) 238 0732
 8254 NW 58th St., Miami, FL. 33166, U.S.A.
 e-mail: sales@armstrongpower.com

www.armstrongpower.com