

ARMSTRONG RENTAL

DIESEL POWERED

25 - 250 kVA GENERATORS

• QUIET • MOBILE • COMPACT • RENTAL GENERATOR SETS

STANDARD FEATURES

- Diesel engine 4-cycle water cooled.
- Brushless, automatic regulated, class H, drip-proof alternator.
- Automatic protection shutdowns.
- Volt selector switch with mechanical and electrical lock.
- Complete and illuminated control panel with electrical meters, engine gauges, Circuit Breaker and Auto-start module.
- Cooling radiator designed for tropical temperatures.
- Quiet rental spec 12 gauge steel enclosure with lifting points.
- Distribution panel with rated load lugs.
- Super critical silencer.
- Heavy-duty skid-type steel base frame.
- Dual fuel supply source; Internal Tank and external connection.
- Electronic speed governor.
- Battery, cables and Battery charger.

OPTIONAL EQUIPMENT

- Fuel Water Separator.
 - Auxiliary Fuel Pump.
 - Sub-Base Fuel Tank.
 - NiCad Battery.
 - Battery Warmer Plate.
 - Space Heater.
 - Temperature Rise Detector.
 - Microprocessor Control Panel.
 - Power Output Receptacles.
 - Trailer.
- Many other options available.




**IVECO
MOTORS**



GENERATOR SET RATINGS

| POWER RATINGS | | AR25LO | AR35LO | AR80IV | AR100IV | AR130IV | AR160IV | AR200IV | AR250IV |
|---------------|------------------|---------|---------|---------|---------|---------|---------|---------|---------|
| OUTPUT | STANDBY (kW/kVA) | 20/25 | 27/34 | 64/80 | 83/104 | 105/131 | 127/159 | 157/196 | 200/250 |
| | PRIME (kW/kVA) | 18/22.5 | 25/31 | 53/66 | 76/95 | 95/119 | 116/145 | 141/176 | 180/221 |
| VOLTAGE | SINGLE PHASE | 240/120 | 240/120 | 240/120 | 240/120 | 240/120 | 240/120 | 240/120 | 240/120 |
| | THREE PHASE | 480/277 | 480/277 | 480/277 | 480/277 | 480/277 | 480/277 | 480/277 | 480/277 |
| AMPERAGE | SINGLE PHASE 240 | 83 | 113 | 267 | 346 | 458 | 446 | 654 | 833 |
| | THREE PHASE 480 | 30 | 41 | 96 | 133 | 166 | 172 | 236 | 301 |
| | THREE PHASE 208 | 69 | 93 | 222 | 250 | 382 | 371 | 545 | 694 |

Ratings: @ 60Hz (1800 rpm). Ratings applicable for both single-phase (1.0 p.f.) and 3-phase (0.8 p.f.) operation. Many industrial, commercial and residential voltages are available. Specifications are subject to change without notice. *1 in. = 2.54 cm; 1 gallon = 3.78 liters. Iveco and the Iveco Logo are registered trademarks of Iveco and Company. Lombardini and the Lombardini Logo are registered trademarks of Lombardini and Company.



ARMSTRONG POWER SYSTEMS

Phone (305) 470 0058 - Fax (305) 470 0068
Toll Free (800) 238 0732
8254 NW 58th St., Miami, FL. 33166, U.S.A.
e-mail: sales@armstrongpower.com

www.armstrongpower.com