

FEATURES

- Armstrong provides one-source responsibility for the generator system and its accessories.
- All units and components are factory tested during prototype and manufacturing stages assuring long product life.
- Generator set accepts one-step 100% of full load per NFPA 110.
- A **one-year** limited **warranty** covers all systems and components. Extended warranties are available.
- Rugged 4 cycle heavy-duty diesel engine, with swirl intake ports for a low fuel consumption and excellent transient response.
- **Generator features:**
 - Unique Volts per Hertz compensated electronic AVR excitation system delivers reliable voltage response for in rush loads.
 - Brushless, rotating-field generator has low reactance, 2/3 pitch, class H insulation, minimizes voltage distortion when powering non-linear loads.
- **More features:**
 - Controllers are available to meet your most demanding applications.
 - In the event of low oil pressure or high coolant temperature the self-protecting system will automatically stop the engine.
 - Aluminum Enclosure Sound Attenuated
 - Integrated fuel Tank

GENERATOR SET RATINGS

Model	Volt Code	Voltage	Winding Connection	Phase	Power Factor	Hz	Amps Standby	Standby kW / kVA	Prime kW / kVA
A50KBS	61	480 / 277	12 - HI WYE	3	0.8	60	60	40 / 50	36 / 45
A50KBS	63	440 / 254	12 - HI WYE	3	0.8	60	66	40 / 50	36 / 45
A50KBS	64	240 / 139	12 - HI DELTA	3	0.8	60	120	40 / 50	36 / 45
A50KBS	65	220 / 127	12 - LOW WYE	3	0.8	60	131	40 / 50	36 / 45
A50KBS	66	208 / 120	12 - LOW WYE	3	0.8	60	139	40 / 50	36 / 45
A50KBS	67	240 / 120	12 - 2 DELTA	1	1.0	60	167	40 / 40	36 / 36
A50KBS	51	415 / 240	12 - HI WYE	3	0.8	50	63	36 / 45	29 / 36
A50KBS	53	380 / 220	12 - HI WYE	3	0.8	50	68	36 / 45	29 / 36
A50KBS	55	220 / 127	12 - LOW WYE	3	0.8	50	118	36 / 45	29 / 36
A50KBS	57	220 / 110	12 - 2 DELTA	1	1.0	50	164	36 / 36	29 / 29

Stand-By ratings are continuous electrical service during the interruption of normal power. No overload capacity is specified at these ratings. Prime ratings available with variable loads are continuous, 10% overload capacity for one hour in twelve hours periods.

Both ratings per BS 5514, DIN 6271, ISO-3046

Many industrial, commercial and residential voltages are available

ALTERNATOR SPECIFICATIONS

Type	Four pole, revolving field
Rotor Insulation	Class H
Temperature Rise	150°C Standby
Material	Epoxy resin
Line-To-Line Harmonic Factor (Max)	5%
Telephone Interference Factor (Tif)	1%
Voltage Regulator	Solid State
Cooling	Self-ventilated and drip proof
Bearing	1 each, pre-lubed
Coupling	Direct, Flexible Disc
Load Capacity (Standby)	100%
Overload Capacity (Prime)	110%
Voltage Regulation	
No Load To Full Load	±1 %
One Step Load Acceptance	
Per NFPA 110	100%

- ❑ Four pole, revolving field, direct coupled to engine flywheel, provides excellent alignment.
- ❑ Insulation is of class H, ready to be used on harsh environments where sea spray, sand and chemical corrosion are existing factors.
- ❑ Voltage regulator provides Volts/Hertz compensation to improve the motor starting capabilities, therefore support the engine handling transient loads.
- ❑ Dynamically balanced rotor, with damper winding, help dissipate transient voltage interference during load variations.
- ❑ The windings have a 2/3 pitch in order to reduce the harmonic content of voltage.
- ❑ Robust mechanical structure permits easy access to connections.

ENGINE SPECIFICATIONS

Manufacturer	Kubota
Model	V3600-T-BG
Bore	3.86in. (98.0mm)
Stroke	4.33in. (110.0mm)
Number Of Cylinders	4
Piston Displacement	202.48 in. ³ (3.318L)
Compression Ratio	23.0:1
Combustion System	IDI
Engine Type	In-Line – 4 Cycle
Aspiration	Turbocharged
Engine Crankcase Vent System	Closed
Cylinder	Borable
Crankshaft Material	Forged Steel
Governor, Make	Mechanical
Frequency Regulation,	
No Load To Full Load	5 %
Air Cleaner	Dry Element

- ❑ Robust, compact, heavy duty Kubota diesel engine, for reliable endurance.
- ❑ Many various accessories available along with power take-off points.
- ❑ Indirect fuel injection system with Kubota E-TVCS Three Vortex Combustion System, reduces emissions and improves fuel consumption.
- ❑ High in Output Low in fuel Consumption.
- ❑ High capacity governor and large size flywheel, makes Kubota engines control the speed regulation within 5%.
- ❑ Super Glow Systems, is standard equipment to help start the engine in cold temperatures, at -4°F (-20°C), the engine will start with only 10 seconds of preheating time.

Powered By: 

STANDARD EQUIPMENT

ENGINE

- Air Cleaner
- Fuel Pump
- Fuel Filter
- Oil Pump
- Full Flow Oil Filter
- Jacket Water Pump
- Thermostat and Housing
- Exhaust Manifold Dry
- Oil Cooler
- Blower Fan & Fan Drive
- Radiator - Unit Mounted
- Electric Starting Motor 12v
- Housing & Flywheel
- Charging Alternator - 12v

- Battery Kit & Battery Rack

GENERATOR

- Synchronous, Brush-less
- Four Pole
- Single Bearing
- Direct Coupled With Flex
- Class H Insulation

CONTROL PANEL

- Digital Control Panel
- Auto Start Module
- Electric Hour Meter
- Stop-Manual-Auto Pushbuttons
- Standard Engine Control

Monitoring

- Automatic Shutdowns
- * High Water Temperature
- * Low Oil Pressure
- *Protective 12vdc Circuit Breaker
- Display For:
 - * Water Temperature
 - * Oil Pressure
 - * Overcrank
 - * Underspeed
 - * Overspeed
 - * Battery Charging

GENERAL

- Critical Muffler
- Flexible Connector
- Rain Cap
- Aluminum Enclosure-White
- Lockable & Removable Doors
- Sound Attenuated
- Mainline Circuit Breaker
- Oil Drainage kit
- Integrated Fuel tank 150 gal
- Battery Charger 5 amp
- In Frame Lifting Points

INSTALLATION AND APPLICATION DATA

	Item	Units	Type of Operation and Application			
			60 Hz		50 Hz	
			Prime	Standby	Prime	Standby
Engine	Rated Speed	rpm	1800		1500	
	Gross Engine Output	bhp (kWm)	63.0 (46.9)	70.0 (52.2)	54.0 (40.3)	60 (44.7)
	BMEP	psi (kPa)	136.9 (943)	152.1 (1048)	140.8 (970)	156.4 (1078)
	Mean Piston Speed	Ft/s (m/s)	21.56 (0.55)		17.9 (0.46)	
Cooling System	Ambient Air Temperature	°F (°C)	122 (50)			
	Engine Heat Reject to Coolant	BTU/min (kW)	2337 (41.1)	2727 (47.9)	2103 (37.0)	2337 (41.1)
	Pusher Fan Air Flow	Cfm (m3)	4750 (134)		3870 (109)	
	Coolant Flow	gal/min (L/min)	21 (80)		15.8 (60)	
	Coolant Capacity	qt (L)	7.7 (8.5)			
	Thermostat Start to Open	°F (°C)	170 (76.5)			
	Thermostat Fully Open	°F (°C)	194 (90)			
	Blower Fan Diameter	in. (mm)	18 (457.2)			
Fuel System	Max. Transfer Pump Suction	ft (m)	3 (0.9)			
	Fuel Type		Diesel #2			
	Fuel Consumption @ 25% Power	gal/hr (L/hr)	0.76 (2.87)	0.85 (3.21)	0.65 (2.46)	0.72 (2.72)
	Fuel Consumption @ 50% Power	gal/hr (L/hr)	1.52 (5.75)	1.69 (6.39)	1.30 (4.92)	1.45 (5.48)
	Fuel Consumption @ 75% Power	gal/hr (L/hr)	2.28 (8.63)	2.54 (9.61)	1.96 (7.41)	2.17 (8.21)
	Fuel Consumption @ 100% Power	gal/hr (L/hr)	3.04 (11.5)	3.38 (12.79)	2.61 (9.87)	2.90 (10.97)
Air Requirement	Combustion Air Flow	ft ³ /min (m ³ /min)	3814 (108)		4750 (134)	
	Air Intake Restriction	In.H ₂ O (kPa)	18.1 (4.5)			
	Exhaust Temperature	°F (°C)	842 (450)		797 (425)	
	Maximum Allowable Back Pressure	In.H ₂ O (kPa)	60.6 (15.1)			
Lubrication System	Specific Oil consumption		0.95g/kW-hr			
	Oil Pan Capacity	qt (L)	13 (14.3)			
	Total Engine Oil Cap. w/filter	qt (L)	14 (15.4)			
	Oil Filter Type		Cartridge			
Engine Electricals	Battery Charging Alternator	Volts, Ground	14V, negative			
	Battery Charging Alternator	Rated amps	45			
	Recommended Battery Cold Crank	CCA amps	600			
	Starter Motor	Volts, Ground	12V, negative			
Operation	Temperature and Altitude Losses		Consult Factory			

OPTIONAL EQUIPMENT

Cooling System

- Remote Radiator
- Jacket Water Heater

Fuel System

- Fuel/Water Separator
- Auxiliary Fuel Pump
- Sub-Base UL Tank 142 Double Wall

Start System

- Battery Nicad
- Battery Warmer Plate
- Battery Charger
 - Automatic Float Equalizing

- Trickle

Switchgear

- Main Line Circuit Breaker
 - Shunt trip
 - Auxiliary switch
- Automatic Transfer Switch
- Paralleling

Generator

- Permanent Magnet Excitation
- Space Heaters

Control Panel

- NFPA 110 Ready
- Remote Annunciation Panel



- Audible Alarm

General

- Spring vibration isolators
- Interior lights AC or DC
- Trailer
- Export Packaging
- Special Testing
- Warranties
 - ____ Year

For Other Options Consult

DIMENSIONS AND WEIGHT



	Units	Sound Att. Unit
Length	In. (mm)	87 (2210)
Width	In. (mm)	37 (940)
Height	In. (mm)	64 (1626)
Weight	Lbs (kg)	1747 (794)

General configuration for reference only, do not use these dimensions for installation purposes. Contact your local dealer for certified drawings.

All Specifications and Materials are subject to change without prior notice.

ARMSTRONG POWER SYSTEMS

ARMSTRONG POWER SYSTEMS LLC
 Phone (305) 470-0058
 Fax (305) 470-0068
 Toll Free (800) 238-0732
 Address: 5100 NW 72 Ave, Miami FL 33166
 Email: sales@armstrongpower.com
www.armstrongpower.com

